

ROUND SLINGS

Wisra Round Slings

made of polyester to fulfil highest standards
with single coat tested according to EN 1492-2 GS
safety factor 7:1

double coat on demand



Order-No.	type	carrying capacity in (kg)	colour	carrying capacity at following applications					
				direct	tied	laid simply	45°	90°	120°
61010 XX 000 27	S X 10	1.000	violet	1.000	800	2.000	1.800	1.400	1.000
61020 XX 000 27	S X 20	2.000	green	2.000	1.600	4.000	3.600	2.800	2.000
61030 XX 000 27	S X 30	3.000	yellow	3.000	2.400	6.000	5.400	4.200	3.000
61040 XX 000 27	S X 40	4.000	grey	4.000	3.200	8.000	7.200	5.600	4.000
61050 XX 000 27	S X 50	5.000	red	5.000	4.000	10.000	9.000	7.000	5.000
61060 XX 000 27	S X 60	6.000	brown	6.000	4.800	12.000	10.800	8.400	6.000
61080 XX 000 27	S X 80	8.000	blue	8.000	6.400	16.000	14.400	11.200	8.000
61100 XX 000 27	S X 100	10.000	orange	10.000	8.000	20.000	18.000	14.000	10.000

XX = perimeter / circumference for example 01 = 1 meter
12 = 12 meter

standard lengths for SX 10, SX 20 = 1,2,3,4,5,6,8,10 m
other types from 3 m on